

## Specialist Film Studio Liner

Insul-Quilt has been manufactured in Los Angeles, California exclusively for the film studios of Hollywood and beyond since the 1960's. Our client list is a "who's who" of the film industry, and we're privileged to be associated with a company that has such a pioneering history and is the first choice film studio liner worldwide.



## Product Specification

Manufactured using two 25mm layers of 24kgs/m<sup>3</sup> density glass fibre, a foil coated backing paper is applied as well as an open weave glass cloth face layer. When stitched together, a duvet like structure is formed. Supplied either in black or white as standard, customised colours are available at an extra cost. A BS476 Class 0 Fire Certification has been achieved.

## Technical Data

### SOUND TEST DATA - PER ASTM 795 TYPE A MOUNTING

#### Noise Reduction Coefficient Type A Test for Insul-Quilt

125	250	500	1000	2000	4000	NRC	
10.2	46.4	70.0	74.3	65.9	58.1	1.01	Sound absorbtion (Sabins)
0.16	0.73	1.09	1.16	1.03	0.91	1.00	Noise Reduction Coefficient 95%

## Installation

Insul-Quilt can be installed in a number of ways. Where the substrate is plasterboard, drywall screws and washers can be used. Where the substrate is more robust, a nail gun can be used. Please refer to the images below showing examples of installation.

